

Flexitallic®

n novus™
a Flexitallic brand

Data / Specification Sheet • Novus 21

Novus 21 is a medium quality compressed sheet material based on aramid fibre with a nitrile rubber binder system.



Service

Novus 21 is a general purpose material suitable for use in a wide range of applications, including hot and cold water, oils, fuels, low pressure steam and a wide range of general chemicals.

Availability

Thickness range:
0.4mm to 6.0mm

Standard sheet sizes:

2.0m x 2.0m
2.0m x 1.5m
2.0m x 1.0m
1.5m x 1.5m
1.5m x 1.0m

Standard roll sizes:

Up to a maximum size of 6.0m x 2.0m


Available with a gauze mild steel wire reinforcement: Novus 21 GWI.

It can also be supplied with anti-stick and graphite coating.

Physical properties

Thickness		1.5mm
Density		2.0g/cc
Tensile Strength	ASTM F152	12MPa
Compression	ASTM F36	8%
Recovery	ASTM F36	50% min
Residual Stress	BS 7531 (300°C)	20MPa
	DIN 52913	27MPa
Gas Leakage	BS 7531	<1.0cc/min
ASTM Oil 1	Thickness increase	1.5%
IRM 903 Oil	Thickness increase	3.0%
ASTM Fuel B	Thickness increase	2.5%

Novus 21 Pressure/Temperature Limits



- 1 Suitable subject to chemical compatibility.
- 2 Suitable in some cases but check your application requirements with Flexitallic.
- 3 Contact the Technical Team for applications with higher temperatures and pressures. Applicable to 1.5mm and below.

The operating temperature of non-asbestos sheet material is related to the thickness of materials selected. Thinner materials give better temperature and pressure properties.

As the company's products are used for a multiplicity of purposes and as the company has no control over the method of their applications or use, the company excludes all conditions or warranties, expressed or implied by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the company and the customer is given for customers assistance only, and without liability on the part of the company.